
GRID MODERNIZATION THROUGH RENEWABLE ENERGY INTEGRATION




We drive industry


We use our capabilities and expertise in developing industrial systems that deliver sustainable performance toward the greater advancement of society. It is our mission to provide "high-quality and advanced products and systems" realizing "comprehensive solutions" for diversified industrial fields in global markets. As an industrial systems integrator, we focus on industrial markets, drive innovation and undertake continuous and concerted effort to meet the requirements of and move forward with our customers.

TMEIC's Capabilities and Expertise Span All Industries

















TOSHIBA

Toshiba Corporation

1875

Tanaka Seisaku-sho (Tanaka Engineering Works) established.

MITSUBISHI

Mitsubishi Electric Corporation

1921

Mitsubishi Electric Corporation established.

TGAJ

Toshiba GE Automation Systems
Corporation

2000

Toshiba and General Electric Company of USA established GE Automation Systems Corporation (TGAJ), for industrial plant systems (steel, paper plants etc.).

TMAE

TMA Electric Corporation

1999

Toshiba Corporation and Mitsubishi Electric Corporation together established TMA Electric Corporation (TMAE), a joint company for the production of large capacity electric motors.


TMEIC

Toshiba Mitsubishi-Electric Industrial Systems Corporation



2003

The industrial systems departments of Toshiba Corporation and Mitsubishi Electric Corporation, TMAE, and TGAJ, were merged to create the Toshiba Mitsubishi-Electric Industrial Systems Corporation (TMEIC).



Global Headquarters

Toshiba Mitsubishi-Electric Industrial Systems Corporation

Tokyo Square Garden, 3-1-1 Kyobashi, Chuo-ku, Tokyo Phone: +81-3-3277-4491 Fax: +81-3-3277-4565

North America

TMEIC Corporation

1325 Electric, RD Roanoke VA 24018 U.S.A. 2060 Coo Drive, Salem, VA 24153 U.S.A. Phone: +1-540-283-2000 Fax: +1-540-283-2001

TMEIC Power Electronics Products Corporation

6102 N. Eldridge Parkway, Houston, TX 77041, U.S.A.

South America

TMEIC Sistemas Inustriais da América do Sul Ltda.

Av. Paulista 1439, Sala 72, Bela Vista 01311-200 Săo Paulo SP, Brazil Phone: +55-11-3266-6161

Fax: +66-11-3253-0697

Europe

TMEIC Europe Ltd.

6-9 The Square, Stockley Park, Uxbridge, Middlesex, UB11 1FW, U.K. Phone: +44-870-950-7220

Fax: +44-870-950-7221

Italy Branch Office

Via Pappacena, 22-70124, Bari, Italy Phone: +39-080-5046190 Fax: +39-080-5042876

Middle East

TMEIC Middle East Branch

5EB-533, Dubai Airport Freezone, P.O.Box 54512, Dubai, United Arab Emirates Phone: +971-4-6091-434 Fax: +971-4-6091-439

Australia

TMEIC Process Technology Application Centre Pty Limited

358 Main Street, Mornington, Victoria, 3931 Australia Phone: +61-3-5977-072

Fax: +61-3-5977-0833

Asia

Toshiba Mitsubishi-Electric Industrial Systems (China) Corporation

21B, In. do Mansion, No. 48A Zhichun Road, Haidian District, Beijing 100098, P. R. China

Phone: +86-10-5873-2277 Fax: +86-21-5873-2208

Shanghai Branch Office

Rm 2603, Shanghaimart, 2299 Yan'An Rd (W), Changning District, Shanghai 200336, P. R. China Phone: +86-10-62360588 Fax: +86-21-62360599

Shanghai Works

No.2161 Huiwang Road, Jiading District, Shanghai 201800, P. R. China Phone:+86-21-3129-6828 Fax:+86-21-3129-6824

No. 2.66 Lijiang Rd. Yancheng Economic & Technological Development Zone, Jiangsu, P.R China

TMEIC Asia Pte. Ltd.

152 Beach Road #13-07/08 Gateway East 189721, Singapore Phone: +65-6292-7226 Fax: +65-6292-0817

PT. TMEIC Asia Indonesia

Gd. Alamanda Tower 23rd Floor #Suite E JL. TB Simatupang Kav.23-24, Cilandak Barat Jakarta Selatan 12430, Indonesia

Phone: +62-21-2966-1699 Fax: +62-21-2966-1689

TMEIC Asia (Thailand) Co., Ltd

Unit 12A03, 12A Floor, AIA Capital Center, 89 Ratchadapisek Road, Dindaeng, Bangkok 10400, Thailand Phone: +66-2045-0512 Fax: +66-2045-0517

Taiwan Office

18F-5, 55 Chung-Cheng 3rd Road, Kaohsiung 800, Taiwan Phone: +886-7-2239425 Fax: +886-7-2239122

TMEIC Industrial Systems India Private Limited

The Millenia, Tower eAF ,10th Floor, # 1&2 Murphy Road, Halasuru, Bangalore – 560 008, India Phone: +91-80-6751-5599 Fax: +91-80-6751-5550


Mumbai Branch

901/D, Filix L,B,S, Road, Opp Asian Paints, Bhandup, West Mumbai, Maharashtra India 400 078 Phone: +91-22-6155-5444 Fax: +91-22-6155-5423

Hyderabad Branch

Unit # 03-01, Third Floor, Block 2, Cyber Pearl, HITEC City, Madhapur, Hyderabad – 500 081, India Tel: +91-40-4434-0000

Fax: +91-40-4434-0034



ENERGY STORAGE SYSTEMS TMEIC




TMEIC is a leading technology & solution provider for stationary Energy Storage System(ESS) including the Battery System(BS), Power Plant Controller(PPC) and the Bidirectional Inverter(PCS).


TMEIC has well over 10 years of experience with global deployment of over 650MWhs. With ground-breaking innovations in power conversion and power plant controller technology, TMEIC brings cutting edge technology to the energy storage market.

With enhanced speed and advanced control logic, the TMEIC energy storage solution can optimize revenue and enhance design and operational flexibility.

Inclusive of power plant controller offering, along with global partnerships, TMEIC energy storage solution can optimize the system design reducing battery oversizing. Additionally, TMEIC's innovative guarantee offering enhances the bankability of the project.



■ ENERGY STORAGE SYSTEM



Specifications

ITEM	SPECIFICATION					
Power	From 570kW per PCS Max. 3.825MW per PCS Line UP					
System Voltage	DC 710 to 1300VDC AC 480 to 630VAC					
Reactive Power		PF 0.80 lagging	to 0.80 leading			
Ramp Capability		Maximum Capac	ity within 500 ms			
Duration and Efficiency	30 min 1 hr 2 hrs 4 hrs > 85% > 88% > 89% > 90%					
Operating Temperature	-20° ~ 50°C					
Altitude	<2000m Up to 3,500m with de-rating					
Seismic Rating	Available ratings up to Zone 4					
Voltage Ride Through	As per National Grid Code and IEC 61727					
Standards Compliance	Meets or exceeds industry standards, including IEEE519, NEC, UL1741, UL1642, UL1973					
Control and Monitoring	ESS control is done by the PPC which includes GUI, HMI, Trace Data, Wireless communication with Inverter, Remote access to site					
External Control Interface	Communication via DNP3, Modbus TCP/IP					
Battery	Lithium Ion NMC					
Equivalent Availability Factor	> 98%					




ENERGY STORAGE SYSTEM

Frequency Response

TMEIC's ESS system is a dynamic frequency response system that automatically acts as a source or sink to the grid depending on the changes and fluctuations in the grid. When the system frequency is high, the ESS acts as a sink, absorbing electricity from the grid and charging its battery system. When the Grid Frequency is below the system frequency, the system acts as a current source, supplying power to the grid. As a result, balance in the system is automatically maintained.


as a Sink



Depending on variation in the Frequency, TMEIC's system supplies active power to the grid as per utility requirement.

Energy Arbitrage

The ESS also acts as a long-term storage of electric energy for supplying power to the grid at a later stage. This allows the energy that is generated now to be enjoyed at a later time depending on the need as well as the commercial pricing of the system.




The duration and the amount of power to be stored and released will depend on the requirement of the system. TMEIC can program the system as per the system needs. Application can be designed in order to meet the Triad requirements, allowing higher rates from the grid to be enjoyed during the peak hours in the evening.

Peak Shaving

The ESS has the capability to provide peak shaving by acting as an instantaneous current source when there is a sudden or scheduled peak in demand. This capability is provided by the power plant controller either automatically or by request from the System operator.

The duration and time of the power output depends on the battery system and the priority of the system. TMEIC can design and integrate the solution depending on the requirements of the


system.



Voltage/Reactive Power Control

In addition to being a current source, the ESS can act as a voltage compensator. This is done by modifying the phase of the voltage and the current. The voltage and reactive power compensation brings stability to the grid.

TMEIC's ESS inverter can provide adequate VAR compensation as required by the National Grid, Grid Code and the Enhanced Reactive Power System. TMEIC's ESS can provide reactive power to the grid within 150ms from receipt of the signal from the Service operator or as required by the system operator.




FEATURE OF TMEIC ESS

Fast Control Response within 100ms


TMEIC believes that response from the point of change observed at the point of interconnection the Inverter would be able to respond within 100ms. This is largely dependent on the meter that is chosen for obtaining the Voltage and current values at the point of interconnection. TMEIC may, based on the application chose to obtain the signals directly from the PT or CT in order to reduce the response time. The details of the design and application shall be discussed and mutually agreed during the detailed design based on the application and purpose of the system.


IGNITION POINT




Remote Control and Monitoring

The collected field Information by TMEIC's Power Plant Controller can be monitored, controlled and troubleshooting locally & remotely. Optimization + Fault Prevention by collecting and analyzing data is being developed using TMIEC Could Server with Power Plant Controller.





PV + ESS HYBRID SYSTEM SOLUTION




PV + ESS HYBRID SYSTEM SOLUTION

The proposed ESS system can provide Renewable integration support as required for PV Plants. The ESS can provide adequate control on the Ramp rate, frequency regulation, PV output smoothening, power limiting, and VAR Compensation. Ramp Rate Control, when enabled, allows the energy storage system to maintain ramp rates in the case of rapid reduction in plant output power regardless of the cause. To perform this function, the PPC computes a minimum SOC needed for ramp rate control. If necessary, the PPC will direct power to the ESS to bring it to the required SOC. The required SOC for performing this function depends on the current plant power output, the programmed site power ramp rate and the total capacity of all the ESS assets.


Ramp Rate Control

When enabled the energy storage system will be used to maintain ramp rates in the case of a rapid reduction in plant output power regardless of the cause. To perform this function the PPC computes a minimum SOC needed for ramp rate control. If necessary the PPC will direct power to the ESS to bring it to the required SOC. The required SOC for this function depends on the current plant power output, the programmed site power ramp rate and the total capacity of all the ESS assets.




Site Power Limit Control


When Site Power Limit Control is enabled and the PV plant is subject to power limits, the PPC will use the ESS to maintain the plant at the power limit whenever irradiance reduces. This feature can also shift plant power production towards the end of each daily production period by extending the time the plant remains in power limit each day. As the PPC maintains the power limit the SOC of the ESS is reduced to the minimum SOC.



PV + ESS HYBRID SYSTEM'S CONCEPTS AND BENEFITS

TMEIC's PV+ESS System concept allows more flexible system design compared to conventional Medium Voltage AC Coupling DC-Coupling or MV-AC coupling system architecture. With decades of design, R&D, and global experience, TMEIC's next generation universal PCS design offers Hybrid Low Voltage AC Coupling.





- Wider reactive power capability range as a system
- Identical PCS for both ESS and PV allows for easier maintenance and spare parts inventory
- Reduce round trip power losses due to Transformer
- Reduced BOS Cost (Reduced V Switchgear, Transformer, no additional cables between modules and storage)
- Flexibility in design and application



Common Platform

TMEIC's newest Inverter is designed with common platform to utilize both PV Inverter and ESS Inverter.

Feature

- · Common platform design
- Highest efficiency (99.0%)*
- Global solution with UL or IEC rated
- Outdoor Compact size
- Various station size (up to 6 parallel inverters)

EDGENERGY ^{TI}	M	BSU-L0630ER	BSU-L0800ER	BSU-L0840ER		
LDGLNLKGT		BSU-L0630GR	BSU-L0800GR	BSU-L0840GR		
	Maximum Power	653kWp@98% Efficiency	816kWp@98% Efficiency	857kWp@98% Efficiency		
DC Input	Maximum Voltage	710Vdc ~ 1300Vd	875Vdc ~ 1300Vdc	915Vdc ~ 1300Vdc		
A.C. Osstanist	Rated Power	640kW/640kVA	800kW/800kVA	840kW/840kVA		
AC Output	Rated Voltage	480V (+10%, -12%)	600V (+10%, -12%)	630V (+10%, -12%)		
	Maximum Current		702Arms @50°C			
	Rated Frequency	50Hz / 60Hz				
	Number of Phases	3 Phase / 3 Wire				
	Maximum Efficiency	99.0%				
General	Enclosure Rating	IP 55 / NEMA 3R				
General	Installation	Outdoor				
	Temperature	-25 ~ 50°C				
	Maximum Altitude		2000m **			
	Communication Type	Modbus TCP				
	Certification Compliance	UL1741, UL174SA / IEEE1547 / NEC2017 IEC62109-1,2 / IEC61000-6-2,4 / IEC61727, IEC62116 / IEC61400, IEC61683 / IEC60068				
	Standard Number of Input	6 (Maximum 8 per Inverter) Each input rating is a maximum of 400A				

^{*}without control power

^{** &}gt;2000m power derating (Max. 4000m)






MPPT TECHNOLOGY

MPPT (Maximum Power Point Tracking) is a technique used to track variation in irradiance in order to maximize energy harvest. MPPT algorithm samples module output power along the I-V curve to stay within the "knee" or the maximum point of the P-V curve. TMEIC has over 20 years of experience in developing and enhancing MPPT technology.

- Proven at Frauhofer Lab, Germany
- Industry's leading 99.9% dynamic MPPT efficiency
- Validated by third party IE for excellence.




TMEIC 3-LEVEL NPS TECHNOLOGY

The 3-level NPS (Neutral Point Switch) topology adopted in TMEIC SOLAR WARE series is the most advanced power conversion technology used in the PV industry. The 3-level NPS technology

enhances the performance and reliability of the 2-LEVEL inverter by evenly distributing the voltage stress levels of the individual switching devices, or IGBT (Insulated Gate Bipolar Transistor). TMEIC has been implementing this technology in the PV industry since 2009, and its effectiveness has been well proven in the solar industry.

Wider DC voltage range → Higher DC/AC ratio acceptable

Lower harmonic distortion → Small Filter Reactor → High Efficiency @low load



50% stress compared to 2-level

Lower Losses & Lower Stress → High Efficiency & High Reliability

We test for reliability under a variety of extreme conditions to ensure long term reliability of the PV inverters.

EXTREME TEMPERATURE

Whether the plant is installed in the Southwest desert of the USA or flat lands of Hokkaido, Japan, TMEICs' inverters can withstand extreme variations in temperature from hot to cold. TMEIC follows IEC-62093 standard and inverters are subjected to -25 to 75C temperature cycle pushing the limit.

I IEC-62093(2005)

- Balance-of system components for photovoltaic systems Design qualification natural environments IEC-60068-2-30(2005)
- Environmental testing Part 2-30: Tests Test Db: Damp heat, cyclic (12 + 12h)cycle IEC-60068-2-78
- Environmental testing Part 2-78: Tests Test Cab: Damp heat, steady state



PV Inverter: High Temperature High Humidity Test



AC Station: Full Load Temperature Rise Test

WATER PROTECTION

TMEIC's outdoor rated PV inverters go through stringent water tightness testing to ensure long term performance in various rain and storm conditions. Tests are witnessed by NRTL and performed per UL-1741 standard.

UL-1741

• UL Standard for Safety Inverters, Converters, Controllers and Interconnection System Equipment for Use With Distributed Energy Resources





I TMEIC AFTER SERVICE


O&M Service

- Customer Support
- Troubleshooting
- Periodic Maintenance

Inverter's Warranty Menu


- Standard Warranty5 Years factory warranty
- Extended Warranty
- We can propose optional plans according to customer needs

Re-order and Edit Content



Service menu and warranty program differs depending on the country / products, please contact us.





Specifications

SOLAR WARE U		PVU-L0800GR PVU-L0800ER	PVU-L0840GR PVU-L0840ER	PVU-L0880GR PVU-L0880ER	PVU-L0920GR PVU-L0920ER	
DC Input	Maximum Power	816kWp@98% 857kWp@98% Efficinency Efficinency		898kWp@98% Efficinency	939kWp@98% Efficinency	
	Maximum Voltage		1500	OVdc		
	MPPT Operation Range	875Vdc ~ 1300Vdc (starting-up from 1450V)	915Vdc ~ 1300Vdc (starting-up from 1450V)	960Vdc ~ 1300Vdc (starting-up from 1450V)	1005Vdc ~ 1300Vdc (starting-up from 1450V)	
	Rated Power	800kW/800kVA	840kW/840kVA	880kW/880kVA	920kW / 920kVA	
AC Output	Rated Voltage	600V (+10%, -12%)	630V (+10%, -12%)	660V (+10%, -12%)	690V (+10%, -12%)	
	Rated Current	702Arms @50°C				
	Rated Frequency	50Hz / 60Hz				
	Number of Phases		/ 3 Wire			
	Maximum Efficiency *		99.	0%		
General	Enclosure Rating	IP 55 / NEMA 3R				
General	Installation	Outdoor				
	Temperature	-25 ~ 50°C				
	Maximum Altitude		2000	m **		
	Communication Type		us TCP			
	Certification Compliance	UL1741, UL174SA / IEEE1547 / NEC2017 IEC62109-1,2 / IEC61000-6-2,4 / IEC61727, IEC62116 / IEC61400, BDEW / IEC61683 / IEC6000 6 (Maximum 8 per Inverter) Each input rating is a maximum of 400A				
	Standard Number of Input					

^{*} Without Control Power

Hybrid Plant Design

It can be used as both PV Inverter and ESS Inverter, and being outdoor modular type enables flexible plant design.

Reducing BOS Cost

Transformer losses and BOS cost can be reduced with LV AC Coupling by using SOLAR WARE U.

Features

- Highest efficiency (99.0%)*
- Independent management with Multi-MPPT
- Wide MPPT range and choice of output voltage
- Global solution with UL or IEC rated
- Outdoor Compact size
- Various station size (up to 6 parallel inverters)
- Night Var
- String monitoring with Wi-Fi (LCD less)

^{**&}gt;2000m power derating (Max. 4000m)





1500V PV Inverted

Specifications

		PVH-L2220E	PVH-L2550E	
	Maximum Power	2267kW	2602kW	
DC Input	Maximum Voltage	1500V	1500V	
	MPPT Operation Range	800V~1300V	915V~1300V	
	Rated Voltage	900V	990V	
	Maximum Current	2844A	2844A	
	Short-circuit Breaking Capacity	4800A	4800A	
	Rated Power	2222kW/2222kVA	2550kW/2550kVA	
AC Output	Rated Voltage	550V(± 10%)	630V(± 10%)	
	Rated Current	2332A	2337A	
	Rated Frequency	50/60Hz(+0.5Hz,-0.7Hz)	50/60Hz(+0.5Hz,-0.7Hz)	
	Number of Phases	3 Phase / 3 Wire	3 Phase / 3 Wire	
	Rated Power Factor	Over 0.99	Over 0.99	
	Power Factor Operating Range	± 0.85	± 0.9	
	Total Harmonic Distortion	5%	5%	
	Maximum Efficiency	98.7% (915V DC Input, PF 1)	98.8% (915V DV Input, PF 1)	
	Estimated CEC Efficiency	98.5% (915V DC Input, PF 1)	98.6% (915V DV Input, PF 1)	
	Short-Circuit Breaking Capacity	50kA	50kA	
General	Enclosure Rating	IP21	IP21	
	Installation	Indoor	Indoor	
	Temperature	-20°C~50°C	-20°C~50°C	
	Humidity	5%~95%	5%~95%	
	Maximum Altitude	2000m	2000m	
	Communication Type	Modbus	Modbus	
	Certification Compliance	GB/T 1994, NB/T 32004	IEC62109-1/-2 IEC61000-6-2/-4	

SOLAR WARE 2220, 2550 is the most optimal 1500Vdc PV inverter designed for Utility Scale PV Plant. SOLAR WARE 2220 features Wide MPPT range, allowing flexible DC PV system design. SOLAR WARE 2550 is one of the largest single PV inverters in the market featuring most compact and high efficiency design, whose high quality and high reliability is ensured by TMEIC.


Wide MPPT model(2.22MW/2.22MVA)

SOLAR WARE 2220 features Wide MPPT range, allowing flexible DC PV system design.

Best-in-class and compact size (1.4MVA/M2) SOLAR WARE 2550 is one of the largest single PV Inverters in the market featuring most compact and high efficiency design, whose high quality and high reliability is ensured by TMEIC.

Features

- High efficiency (98.7%)
- Wide MPPT model (2.22MW/2.22MVA)
- Best-in-class and compact size (1.4MVA/M2)
- No derating up to 50°C
- VAR mode for night operation
- Negative grounding (optional)
- DC Box integrated
- Safety function of DC input circuit system





4MVA or 4.4MVA AC Station 380V or 418V 50Hz/60Hz 3 Phase / 3 Wire PVL-L1000E or x16 PVL-L1100E-H PVL-L1000E or x16 PV MODULE PVL-L1100E-H PVL-L1000E or x16 PVL-L1100E-H PVL-L1000E or 12-34.5kV(depends PVL-L1100E-H

Specifications

		PVL-L1000E	PVL-L1000E-H	PVL-L1100E-H
	Maximum Power	1020kW	1020kW	1120kW
DC Input	Maximum Voltage	1000V	1000V	1000Vdc
	MPPT Operation Range	550V~950V	605V~950V	605~950Vdc
	Rated Voltage	655V	655V	655V
	Maximum Current	1855A	1687A	1855A
	Short-circuit Breaking Capacity	50kA	50kA	50kA
	Rated Power	1000kW/1000kVA	1000kW/1100kVA	1100kW/1100kVA
AC Output	Rated Voltage	380V(± 10%)	418V (± 10%)	418V (± 10%)
-	Rated Current	1519A	1519A	1519A
	Rated Frequency	50/60Hz (± 1%)	50/60Hz(+1%)	50/60Hz (± 1%)
	Number of Phases	3 Phase / 3 Wire	3 Phase / 3 Wire	3 Phase /3 Wire
	Rated Power Factor	Over 0.99	Over 0.99	Over 0.99
	Power Factor Operating Range	± 0.9	± 0.9	± 0.9
	Total Harmonic Distortion	5%	5%	5%
	Maximum Efficiency	98.7% (550V DC Input, PF 1)	98.7% (650V DC Input, PF 1)	98.7%
	Estimated European Efficiency	98.3% (550V DC Input, PF 1)	98.3% (650V DC Input, PF 1)	98.3% (650V DC Input, PF 1)
	Short-Circuit Breaking Capacity	65kA	65kA	65kA
General	Enclosure Rating	IP20	IP20	IP20
	Installation	Indoor	Indoor	Indoor
	Temperature	-20°C~50°C	-20°C~50°C	-20°C~50°C
	Humidity	5%~95%	5%~95%	5%~95%
	Maximum Altitude	2000m	2000m	2000m
	Communication Type	Modbus	Modbus	Modbus
	Certification Compliance	IEC62109-1/-2 IEC62109-6-2/-4	IEC62109-1/-2 IEC62109-6-2/-4	IEC62109-1/-2 IEC62109-6-2/-4
	Grid Code			

In terms of reliability, efficiency and productivity, SOLAR WARE 1000 redefines the PV utility scale solar inverter solution. TMEIC sets the standard for utility scale installation with its own proprietary and the 3-level NPS (Neutral-Point-Switched) inverter system, a solution that brings flat efficiency characteristics providing differentiated benefit for high DC/AC ratio projects.

The SOLAR WARE 1000 is a highly engineered 1000V PV inverter suitable for mega-solar power plant deployment. TMEIC's proprietary 3-level topology maximizes utility scale PV system performance and design practice with its industry's leading efficiency level and smallest footprint.

New technology innovation

- Proprietary 3-level NPS (Neutral-Point-Switched) IGBT architecture reduces switching loss and enhances performance through filter reactor size optimization
- Industry's leading 98.7% efficiency
- Wide DC MPP window allowing string sizing flexibility


Optimization of operational expenditure

• All detailed fault waveform data are stored in SD memory card



SOLAR WARE 2500, 2700, 3200, and 3360 are among the largest central PV inverters in the 1500V power class. They feature the first heat-pipe based hybrid cooling technology implemented in utility-scale PV inverter solution, providing optimal opex model.

Specifications





New technology innovation

- Proprietary 3-level NPS IGBT architecture provides reduction on switching loss and performance enhancement through filter reactor size optimization
- Industry leading 98.8% efficiency


World's first heatpipe technology in utility-scale PV inverter

- Utilizing TMEIC heat-pipe technology, the inverter runs without fan operation up to 50% load
- Heat-pipe cooling significantly simplifies thermal management, because it uses fewer parts and only a slow-speed fan with a heat-pipe heat sink

Easy System Integration

• Full direct bus connection both on DC and AC side provides easy installation on-site





SOLAR WARE 1833 is one of the largest central PV inverters in the 1000V power class. It features the first heat-pipe based hybrid cooling technology implemented in utility-scale PV inverter solution, providing optimal opex model.

Specifications

		PVL-L1833GRQ	PVL-L1833GRM	PVL-L1833ERM
	Maximum Power	1710kW	1870kW	1870kW
DC INPUT	Maximum Voltage	1000V	1000V	1000Vdc
	MPPT Operation Range	605V~950V	605V~950V	605~950Vdc
	Rated Voltage	655V	655V	655V
	Maximum Current	2826A	3091A	3091A
	Short-circuit Breaking Capacity	10kA	10kA	10kA
	Rated Power	1667kW/1833kVA	1833kW/2000kVA	1833kW/2000kVA
AC OUTPUT	Rated Voltage	418V (+10%/-12%)	418V (+10%/-12%)	418V (+10%/-10%)
	Rated Current	2532A	2532A	2532A
	Rated Frequency	60Hz (+0.5Hz,-0.7Hz)	60Hz (+0.5Hz, -0.7Hz))	50/60Hz (± 1Hz)
	Number of Phases	3 Phase / 3 Wire	3 Phase / 3 Wire	3 Phase / 3 Wire
	Rated Power Factor	Over 0.99	Over 0.99	Over 0.99
	Power Factor Operating Range	± 0.9	± 0.9	± 0.92
	Total Harmonic Distortion	5%	5%	5%
	Maximum Efficiency	98.8% (605V DC Input, PF 1)	98.8% (605V DC Input, PF 1)	98.8% (605V DC Input, PF 1)
	Estimated ECE Efficiency	98.5% (605V DC Input, PF 1)	98.5% (605V DC Input, PF 1)	98.5% (605V DC Input, PF 1)
	Short-Circuit Breaking Capacity	65kA	65kA	65kA
GENERAL	Enclosure Rating	NEMA3R	NEMA3R	IP44/IP54 (Electronic Circuit)
	Installation	Outdoor	Outdoor	Outdoor
	Temperature	-20°C~50°C	-20°C~50°C	-20°C~50°C
	Humidity	5%~95%	5%~95%	5%~95%
	Maximum Altitude	2000m	2000m	2000m
	Communication Type	Modbus	Modbus	Modbus
	Certification Compliance	UL1741	UL1741	IEC62109-1/-2 IEC62109-6-2/-4
	Grid Code	IEEE1547	IEEE1547	

New technology innovation

- Proprietary 3-level NPS IGBT architecture reduces switching loss and enhances performance through filter reactor size optimization
- Industry's leading 98.8% efficiency
- Wide DC MPP window allowing string sizing flexibility

World's first heatpipe technology in utility-scale PV inverter

- Utilizing TMEIC heat-pipe technology, the inverter runs without fan operation up to 50% load
- Heat-pipe cooling technology significantly simplifies thermal management, because it uses fewer parts and only requires a slow-speed fan with a heat-pipe heat sink

Easy System Integration

• Full direct bus connections on both DC and AC sides provide easy installation on-site



Specifications

		1000V SOLUTION		1500V SOLUTION				
		2MW	4MW	2.22MW	2.55MW	4.44MW	5.10MW	
Container	Туре	30'HC	ISO Standard size 40'HC	ISO Standard size 20'		ISO Standar	ISO Standard size 40'HC	
	Outline Dimensions (L×W×H, m)	9.1 X 2.4 X 2.9	12.0 X 2.4 X 2.9	6.1 X 2.4 X 2.6			12.0 X 2.4 X 2.9	
lavoutou	Туре	PVL-L1000E-H	PVL-L1000E-H	PVH-L2220E	PVH-L2550E	PVH-L2220E	PVH-L2550E	
Inverter	Quantity (pc)	2	4	1	1	2	2	
DC Box	(Integrated in Inverter					
	Grid Voltage			11 / 22 / 34.5kV ± 2	.5%			
	Rated Frequency	50 / 60Hz						
MV Transformer	Number of Phase	Three - phase						
	Standard Compliance	IEC 60076						
	Rated Compliance	12 / 24 / 36kV						
	Rated Frequency	50 / 60Hz						
	Number of Phase	Three - phase						
MV Switchgear	Model	Breaker protection as standard						
	Rated Current	630A as standard						
	Standard Compliance	IEC 62271-1, -100, -102, -105, -200						
LV Pane	Is		Low vo	ltage distribution panels, outlets (Type	depends on the requirements)			
Connecti	on		Connection / ca	bling between LV panels, Inverter, MV t	ransformer, MV switchgear is include	d		
Cooling Me	thod		Force cooling with louvres and fans					
	Transformer	Three-phase, 50/60Hz, less than 10kVA as standard						
Auxilary	Lighting	Lamps						
, , , , , , , , , , , , , , , , , , , ,	Safety Equipments	Gloves, insulation mat						
	UPS	UPS can be supplied as an option						
	Maximum Altitude		Inverter : Up to 2,000m as standard transformer and RMU : 1,000m as standard (Up to 2,000m)					
Environmental Condition	Ambient Temperature	Inverter : -20~40°C as standard (Up to 50°C as option)* 2 Transformer and RMU : -20~40°C as standard (Up to 50°C as option)						
	Relative Humidity	Less than 95% (Not condensating)						

